



DILUNETT®

PAINT AND COATINGS REMOVER

| Product description | <p>DILUNETT® is a powerful, water washable solvent free paint stripper that will remove any oil and alkyd based paint, varnish or woodstain. Requiring no supervision or immediate removal of the softened coating, DILUNETT® strips up to 8 coats of finish in one application. Suitable for virtually any surface including wood, metal, plastic and GRP, DILUNETT®'s gel consistency means it will not run, making it ideal for vertical surfaces and elaborate plaster or wood designs needing to be stripped.</p> <p>Easy to apply, DILUNETT® dissolves paint in the smallest recess and on the finest detail, softening all accumulated layers for simple, clean removal. VOC free and non flammable, DILUNETT® is safe to use in poorly ventilated or confined areas.</p> | | | | | | | | | | | | |
|---------------------------------------|--|-----------|-----------|---------|---------|---------------------------------------|----------|-----------|-----------|-------------------------------------|--|--|--|
| Properties | <ul style="list-style-type: none"> • Solvent free - No toxic fumes. • Easily removed with water. • DILUNETT® is safe on all surfaces except aluminium. • Does not harm plastic. Safe on gelcoat. • Removes up to 8 coats of paint in one operation. • Does not evaporate - Long active work time. • Easy to apply. Gel - Does not run. | | | | | | | | | | | | |
| Basic uses | <ul style="list-style-type: none"> • For exterior use only. • Removes varnishes, stains, paints... • Works on metal**, wood**, plastic, gelcoat, stone, cement... • Horizontal or Vertical surfaces. <p style="text-align: right;">** See "Restrictions"</p> | | | | | | | | | | | | |
| Technical data | <p>Biodegradability: Easily Biodegradable. Certificate Number: OECD 301 F.</p> <p>Viscosity: Gel.</p> <p>Specific Gravity at 20°C (68°F): 1.10 ± 0.05.</p> <p>Physical State: Viscous liquid.</p> <p>Flammability: Not classed as flammable.</p> <p>Shelf Life: 18 months in original unopened container.</p> <p>Container Size: 500ml, 1L, 2.5L, 10L.</p> <p>Appearance & Odour: Creamy, caustic soda smell.</p> <p>Average working times:</p> <table border="1" data-bbox="464 1328 1469 1420"> <thead> <tr> <th></th> <th>1 coat</th> <th>2 coats</th> <th>3 coats</th> </tr> </thead> <tbody> <tr> <td>Alkyd/Oil paint, stains and varnishes</td> <td>5-15 min</td> <td>10-30 min</td> <td>15-45 min</td> </tr> <tr> <td>Acrylic paint, stains and varnishes</td> <td colspan="3">Test on small area to determine working time</td> </tr> </tbody> </table> <p>Note: The above are average working times only. A test should be carried out to determine the actual contact time required to remove the requisite number of coats.</p> <p>VOC: Out of scope.</p> | | 1 coat | 2 coats | 3 coats | Alkyd/Oil paint, stains and varnishes | 5-15 min | 10-30 min | 15-45 min | Acrylic paint, stains and varnishes | Test on small area to determine working time | | |
| | 1 coat | 2 coats | 3 coats | | | | | | | | | | |
| Alkyd/Oil paint, stains and varnishes | 5-15 min | 10-30 min | 15-45 min | | | | | | | | | | |
| Acrylic paint, stains and varnishes | Test on small area to determine working time | | | | | | | | | | | | |
| Restrictions | <p>DILUNETT® will not remove the following types of coatings 2 pack or baked on paints. Polyurethane paint and varnish.</p> <p>Do not use on "weak" woods such as veneers.</p> <p>Do not use on aluminium.</p> | | | | | | | | | | | | |
| Application tools | <p>Flat blade.</p> <p>Synthetic brush.</p> <p>Synthetic roller cover.</p> <p>Synthetic scrubbing brush.</p> | | | | | | | | | | | | |
| Good application practice | <p>Always carry out a preliminary test to determine the contact time required for stripping.</p> <p>Wear chemical resistant gloves, safety goggles and protective clothing.</p> <p>When stripping vertical surfaces, work from bottom to top to avoid streaking.</p> <p>For best results on wood, do not let DILUNETT® work longer than required to dissolve the paint.</p> <p>Hardwoods, especially those rich in tannins (Teak, Oak, Sapele, Cedar...) can turn dark if in prolonged contact with DILUNETT®.</p> <p>Where DILUNETT® has darkened the wood DO NOT allow it to dry, prior to using NET-TROL®*.</p> <p>Treat stripped wooden surfaces with NET-TROL®* to restore the woods colour.</p> <p>Cover and protect everything you do not wish to strip, including plants, shrubs and any aluminium surfaces.</p> <p>Apply between 5°C (41°F) and 35°C (95°F). Do not apply in direct sunlight or to a hot surface.</p> <p>Do not allow DILUNETT® to dry on the surface. If drying occurs dampen with mist application of water.</p> <p>Consult us for additional information and advice prior to using DILUNETT® on Oak and Chestnut.</p> | | | | | | | | | | | | |

| | |
|----------------------------|---|
| Surface preparation | Remove any loose and flaking paint. Brush off any physical surface contamination e.g. moss, general dirt etc. |
| Application | Apply a thick coat of DILUNETT® over the whole surface to be stripped. For woods rich in tannins, work large areas in zones to avoid excessive darkening of the wood. Allow product to work. Remove DILUNETT® and dissolved paint with a stiff scrubbing brush or paint scraper while flushing with water, alternatively use a pressure washer (max 60bars / 870psi). NB: The use of hot water makes the job easier. Thoroughly rinse surface with fresh clean water. After stripping and rinsing. All porous (Wood, Stone, Brick....) surfaces must immediately be treated with NET-TROL®* while still wet to neutralise the surface and restore the woods colour. NB: Consult us for additional information and advice prior to using DILUNETT® on Oak and Chestnut. |
| Neutralisation | Always neutralise stripped wooden and porous (Brick, Stone, Concrete....) surfaces with NET-TROL®*. |
| Coverage | 4 m2 per litre. Actual coverage will vary depending on application method, type, texture, age and porosity of the wood. |
| Clean-up | Water. |
| Storage | Store unused product in original container only. Do not store in metal containers. Keep from freezing and high temperatures. |
| General information | Every care is taken to ensure that the information provided in this technical data sheet is accurate. Owatrol International is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advice and information please contact our technical department by email at info@owatrol.com or the local Owatrol Agent for your country. The information above is correct at the date of issue. All other OWATROL products named in this document should be used as per label instructions and the technical data sheet. |
| Safety | Refer to the safety data sheet (MSDS) available at www.owatrol.com and text on the packaging. Keep out of the reach of children. |
| Issue date | May 2018 |

* Same manufacture.

OWATROL INTERNATIONAL SLU
Barcelona – Spain
Tel. +34 93 125 88 68
Fax +34 93 106 02 13



Find all our solutions:
www.owatrol.com