

L Root

the complete roofing system

100% Silicone Roof Coatings

Puts an end to leaks and future proofs your roof.

Get all the benefits of replacing your roof for only half the cost with OWL seamless silicone roof coating.

OWL Roof offers a full line of silicone roofing products that improve roof performance and extends the life of your flat roof.

- Formula based off professional-grade roof coatings
- Used in the commercial industry for over 20 years
- Easy installation: Clean, Prep, Coat
- 100% silicone, flexible, does not crack
- Unaffected by ponding water
- Waterproofs your roof
- Resists wash-off in rain
- Will not chalk, degrade, or haze from UV exposure
- Environmentally friendly
- No need for any more silver reflective paint
- Maintenance Free







Our 100% silicone roof coating adheres to nearly any aged roof.

Why Choose OWL Roof?

Our high-solids, low odour, single-component, 100% silicone roof coating offers unparalleled waterproofing performance. It is extremely flexible, cures rapidly (2-6 hours), and resists oxidation, severe weather, ozone, UV rays, and many chemicals that can damage your roof.

OWL Roof, a rubber-like seamless coating extends the life of your roof and improves your roof's performance with its superior UV resistance, high tensile strength and extremely low VOC content, all with an extremely environmentally friendly formula.

- Weathered Felt
- Aged asphalt
- Metal, Gutters & **Valleys**
- PVC
- Smooth surface BUR
 SPF
- Silicone coated roof
- EPDM
- Hypalon

- Garage & Extentions
- Mobile Home / Caravan
- Camper VAN
- Concrete
- Granulated cap sheet
- TPO
- Torchdown Felt











OWL 100% Silicone Roof Coating is available in 1, 2 and 5 Gallons U.S. **Colour: Dark Grey**

OWL Roof lasts for decades

OWL Roof

the complete roofing system

100% Silicone Roof Coatings

1. CLEAN: Power wash the roof to remove dirt, Debris, old peeling paint. Any areas of grease contamination are to be cleaned with an industrial strength detergent. Be sure roof is completely free of debris and dry before moving on.




2. PREPARATION: Repair all seams, flashings, drains, and fasteners with Flashing Grade Silicone and or Polyester Reinforcing Tape used with OWL Roof. Some surfaces may require a primer - see below right.



3. COAT: Apply OWL Roof Silicone Coating with a squeegee, roller or brush. As you are applying the coating, check your coating thickness and coverage rate. For additional protection and longer life, add an extra coat of OWL Roof.



4. CLEAN UP: Clean all tools with mineral spirits. Do not use water. Properly dispose of any unused OWL Roof Silicone products in accordance with local regulations.



OWL Roof provides a full line of silicone coatings, accessories, and primers to provide you with a complete roofing system:



100% Silicone Roof Coating System

- One coat on to most surfaces no primer
- Professional grade formula
- Seamless roof waterproofing system

Product	Colour	UPC	Size	Coverage
100% Silicone Roof Coating	Gray	736902581827	1 Gallon	5 m²
100% Silicone Roof Coating	Gray	736902581834	2 Gallon	10 m²
100% Silicone Roof Coating	Gray	736902581841	5 Gallon	25 m²



Flashing Grade Silicone Sealant

- Resists ponding water
- Apply thick, vertical, or upside-down, and it will hold
- Fibre reinforced silicone for voids, cracks etc

Product	UPC	Colour	Size	Coverage
Flashing Grade Silicone Sealant	736902582213	White	1 Gallon	As Reqd



Polyester Reinforcing Fabric

• Imbedded in OWL Roof, adds strength to stress joints, flashings, roof seams and cracks.

1.100000000			Size	
Polyester Reinforcing Fabric	736902581588	White	6"x180FT Roll	As Reqd



EPDM Rinseable Primer

- Prep entire roof in half an hour
- Completely soluble in water

Product	UPC	Colour	Size	Coverage
EPDM Rinseable Primer	736902582220	Pink	1 Gallon	45 m²



Single-Ply Primer

- Improves coating adhesion over all single-ply surfaces
- Plasticiser free

Product	UPC	Colour	Size	Coverage
Single-Ply Primer	736902582237	Black	1 Gallon	18 m²



OWL Waterproofing Systems

For more information on OWL Roof, contact us at

tel: +353 86 067 8603

Or visit us at www.globalcoatings.eu











